

stop crime fast with the

SENTINEL S55

COMPACT | EFFECTIVE | VERSATILE | ECONOMICAL



sen-ti-nel n. A guard whose job is to stand and keep watch

**Suitable for a
wide range of
applications**

**Quality assured
performance
and reliability**

**Simple
installation and
integration**

The Smoke Screen Sentinel range has been designed and manufactured for permanent installation either as a fully integrated part of an intruder alarm system or as a stand-alone system. The range comprises some of the most advanced security smoke generators in the world.

The new, precision engineered heater block offers high performance levels and reliability. This translates to a more impressive volume of drier fog (no residue) that lasts for even longer.

The Sentinel S55 boasts a new feature called Turbo Mode providing maximum protection in risk critical areas. It has a minimum off-mains capability of 1 hour giving you peace of mind should you encounter power difficulties.

New PCB technology, ergonomic connectors and multi-bracket design make installation easy and straightforward. Other features such as the internal battery back-up and enough fluid capacity make the S55 incredibly versatile.



'ANTI-RAID' FIRST BURST

Turbo mode for maximum smoke generation in risk critical areas designed to stop thieves in their tracks.

VERSATILITY IS KEY

Compact and inexpensive, suitable for private homes, server rooms, small offices, stores, window displays and more.

MULTI-NOZZLE OPTIONS

A range of different nozzles are available to produce a range of different effects. This makes installation even easier.

FEATURES

- 5-year warranty
- Full heater redundancy protects against critical failure
- Turbo mode for maximum smoke generation in risk critical areas
- 90 second initial burst for maximum smoke generation in risk critical areas
- Min. 1 hour off-mains operational capability
- Energy save mode cuts costs in periods when the generator is not immediately needed
- IP interface available
- Supports automatic re-firing via screen-sensor technology
- Extreme temperature operation: -10°C to 50°C

OPERATION

- 4 inputs and 7 outputs
- LCD status display and on-board event log

CONSTRUCTION

- Rugged and compact steel casing in white/black
- Environmental pack for installation in confined spaces with elevated ambient temperatures

STANDARDS COMPLIANCE

- EN50131:8 and IEC62642:8
- CNPP Rating: Class I Category 30

FLUID

- 1000ml Swift Fit Bottle

DATA

- 36.8(H) x 13.8(D) x 23.1(W) cm
- Weight: 12 kg (pre-install), 14.5 kg (installed)

CAN'T SEE IT? CAN'T STEAL IT!